



FEATURES:

- *Quality/ reel: 500PCS
- *High rated current & low DCR, quadrate 12.5mm MAX Height 6.0mm MAX
- * Carrier tape packing, use for SMT
- * Suitable for reflow soldering
- * Widely used in DC-DC converter/ LCD TV/ Notebook/ PDA/ MP3 / MP4 Player/ Digital camera/ Portable CDR-W etc.

Electrical Characteristics

电气特性

Model No. 部品名	Test Condition 测试条件	Inductance 电感	Tolerance 公差 (%)	DC Resutance 直流电阻 MAX(W)	Rate Current 额定电流(A)
SDRH125-1R0MC	100KHz,0.3V	1	±20	0.01	8
SDRH125-2R2MC	100KHz,0.3V	2.2	±20	0.014	7.8
SDRH125-3R3MC	100KHz,0.3V	3.3	±20	0.014	8
SDRH125-8R2MC	100KHz,0.3V	8.2	±20	0.021	4.4
SDRH125-100MC	1KHZ,0.3V	10	±20	0.025	4
SDRH125-120MC	1KHZ,0.3V	12	±20	0.027	3.5
SDRH125-150MC	1KHZ,0.3V	15	±20	0.03	3.3
SDRH125-180MC	1KHZ,0.3V	18	±20	0.034	3
SDRH125-220MC	1KHZ,0.3V	22	±20	0.036	2.8
SDRH125-270MC	1KHZ,0.3V	27	±20	0.051	2.3
SDRH125-330MC	1KHZ,0.3V	33	±20	0.057	2.1
SDRH125-390MC	1KHZ,0.3V	39	±20	0.068	2
SDRH125-470MC	1KHZ,0.3V	47	±20	0.075	1.8
SDRH125-560MC	1KHZ,0.3V	56	±20	0.11	1.7
SDRH125-680MC	1KHZ,0.3V	68	±20	0.12	1.5
SDRH125-820MC	1KHZ,0.3V	82	±20	0.14	1.4
SDRH125-101MC	1KHZ,0.3V	100	±20	0.16	1.3
SDRH125-121MC	1KHZ,0.3V	120	±20	0.17	1.1
SDRH125-151MC	1KHZ,0.3V	150	±20	0.23	1
SDRH125-181MC	1KHZ,0.3V	180	±20	0.29	0.9
SDRH125-221MC	1KHZ,0.3V	220	±20	0.4	0.8
SDRH125-271MC	1KHZ,0.3V	270	±20	0.46	0.75
SDRH125-331MC	1KHZ,0.3V	330	±20	0.51	0.68
SDRH125-391MC	1KHZ,0.3V	390	±20	0.69	0.65
SDRH125-471MC	1KHZ,0.3V	470	±20	0.77	0.58
SDRH125-561MC	1KHZ,0.3V	560	±20	0.86	0.54
SDRH125-681MC	1KHZ,0.3V	680	±20	1.2	0.48

特长:

- * 数量/ 卷: 500PCS
- * 耐大电流, 低直流抵抗, 方形 12.5mm MAX 高度 6.0mm MAX.
- * 使用载带包装运用于 SMT.
- * 适用于回流焊 SMT 工艺.
- * 广泛应用于降压转换器, 液精显示, 笔记本电脑, 个人掌上记事本, MP3/ MP4 播放器, 数码相机, 便携式光碟机等等.

Inductance Range/ 电感范围: 1.0- 680 mH

Temperature Range/ 使用温度: -30- 100°C

RoHS Compliant SGS Certified Result					
Pb	Cd	Hg	Cr+6	PBBs	PBDEs
<1000ppm	Nd	Nd	Nd	Nd	Nd

- (1) Inductance is measured with a LCR meter:
HP4284-A (Agilent)/ 3532-50 (HIOKI) or equivalent.
Test frequency at 100kHz/ 1 KHz.
- (2) DC resistance is measured with a Digital Multimeter
TH2512B (TongHui) or equivalent.
- (3) The DC Bias Test with TH2817 & TH1775 (Tong Hui)
The maximum allowable current is a DC current which causes initial inductance to decrease by 25%,
or temperature to rise by 40, whichever is smaller.
(At ambient reference temperature: 20°C)

- (1) 电感直测试仪: HP4284A (Agilent)/ 3532-50 (HIOKI) 或同等 LCR METER. 测试频率 100KHz/1KHz.
- (2) 直流电阻测试仪: TH2512B 或同等的 DCR 测试设备.
- (3) 最大容许电流测试: TH2817 & TH1775; 最大容许电流
定义: 电感下降 25%或温度上升 40 时取其小值作为最大容许电流. (周围环境温度 20°C)