



## FEATURES:

- \* Quality/ reel: 800PCS
- \* High rated current & Low DCR, octagonal 8.3mm MAX Height 4.5mm MAX
- \* Carrier tape packing, use for SMT
- \* Suitable for reflow soldering
- \* Widely used in DC-DC converter/ LCD TV/ Notebook/ PDA/ MP3 / MP4 Player/ Digital camera/ Portable CDR-W etc.

**Inductance Range/ 电感范围:** 2.0- 100 mH

**Temperature Range/ 使用温度:** -30- 100°C

## Electrical Characteristics

### 电气特性

## 特长:

- \* 数量/ 卷: 800PCS
- \* 耐大电流, 低直流抵抗, 八角形 8.3MAX 高度 4.5mm MAX
- \* 使用载带包装运用于 SMT.
- \* 适用于回流焊 SMT 工艺.
- \* 广泛应用于降压转换器, 液精显示, 笔记本电脑, 个人掌上记事本, MP3/ MP4 播放器, 数码相机, 便携式光碟机等等.

RoHS Compliant SGS Certified Result					
Pb	Cd	Hg	Cr+6	PBBs	PBDEs
<1000ppm	Nd	Nd	Nd	Nd	Nd

(1) Inductance is measured with a LCR meter:

HP4284-A (Agilent)/ 3532-50 (HIOKI) or equivalent.  
Test frequency at 100kHz/ 1 KHz.

(2) DC resistance is measured with a Digital Multimeter  
TH2512B (TongHui) or equivalent.

(3) The DC Bias Test with TH2817 & TH1775 (Tong Hui)  
The maximum allowable current is a DC current which causes initial inductance to decrease by 25%, or temperature to rise by 40, whichever is smaller.  
(At ambient reference temperature: 20°C)

(1) 电感直测试仪: HP4284A (Agilent)/ 3532-50 (HIOKI) 或同等 LCR METER. 测试频率 100KHz/1KHz.

(2) 直流电阻测试仪: TH2512B 或同等的 DCR 测试设备.

(3) 最大容许电流测试: TH2817 & TH1775; 最大容许电流  
定义: 电感下降 25%或温度上升 40 时取其小值作为最大容许电流. (周围环境温度 20°C)

Model No. 部品名	Test Condition 测试条件	Inductance 电感	Tolerance 公差 (%)	DC Resutance 直流电阻 MAX(W)	Rate Current 额定电流(A)
SDRH8D43-2R0MC	100KHz,0.3V	2	±20	14	5.5
SDRH8D43-3R9MC	100KHz,0.3V	3.9	±20	19	4.5
SDRH8D43-4R7MC	100KHz,0.3V	4.7	±20	22	4.1
SDRH8D43-6R8MC	100KHz,0.3V	6.8	±20	25	3.9
SDRH8D43-100MC	100KHz,0.3V	10	±20	36	3.2
SDRH8D43-150MC	100KHz,0.3V	15	±20	53	2.3
SDRH8D43-220MC	100KHz,0.3V	22	±20	75	1.8
SDRH8D43-330MC	100KHz,0.3V	33	±20	125	1.4
SDRH8D43-470MC	100KHz,0.3V	47	±20	150	1.3
SDRH8D43-680MC	100KHz,0.3V	68	±20	240	1
SDRH8D43-101MC	100KHz,0.3V	100	±20	360	0.8